



REMOVE SHIPPING FILLER
AFTER INSTALLATION BUT
BEFORE INSERTING FLASHING

INSERT FLASHING
INTO REGLET

PRE-PUNCHED
HOLES FOR FASTENERS

SECURE REGLET TO
WOOD FORM WITH
DUPLEX NAILS

WOOD FORM (REMOVED
AFTER CURING)

PRIMARY OPTIONS:

METAL: _____
GAUGE: _____

GENERAL NOTES:

1. SEE CHENEY SNAP LOCK CAP FLASHING FOR RELATED PRODUCT.
2. LAP RITE SEALANT AVAILABLE.
3. 8'-0" LENGTHS STANDARD.

DIMENSION 'A': N/A	DIMENSION 'B': N/A	DIMENSION 'C': N/A	ANGLE '1': N/A	TYPE:	DRIP HEM: N/A	LENGTH:
CUSTOMER:	PROJECT:	LOCATION:	DATE:	SCALE: NONE	QUANTITY:	

CHENEY FLASHING, LLC

12100 BALTIMORE AVE
SUITE 4
BELTSVILLE, MD 20705

PHONE: 301-931-2556
FAX: 301-931-2559
EMAIL: info@cheneyflashing.com

**REGLET - TYPE 'C'
CONCRETE**

DIMENSIONS NOT TO SCALE. PLEASE CONTACT CHENEY FLASHING COMPANY TO PREPARE A FORMAL PROPOSAL WITH FULLY DETAILED DRAWINGS, PRICING, AND TERMS. © CHENEY FLASHING COMPANY



RE-3